

# TECHNICAL DATA SHEET

## ULTIMATE Fade Out Thinner Aerosol






Date: 18-Jan-2024

**DESCRIPTION**

FL6028/A **ULTIMATE Fade Out Thinner** aerosol is a top quality thinner designed to allow blending of fresh lacquer or 2K finishes into existing paint work. It is a fast drying blending solution used to fade out edges of clearcoats and 2K solid colours.

Do Not Use ULTIMATE Fade Out Thinners over synthetics, nitrocellulose or thermoplastic acrylic finishes.

**Composition:** Fade Out Thinners  
**Colour:** Colourless  
**Shelf life:** 12 months in unopened container  
**Pack size:** 400ml Aerosol Can

	Health and safety “For professional use only” Important: When using any new product, consult the “Health and Safety” data sheet. Always read the risks and precautions stated on the product label.
	Shake can well before use 2-3 minutes.
	Apply product spraying 15-20cm away from the panel being sprayed. DO NOT overload product onto the panel.
	Apply thin coats in contact points of the old paint coat and the newly applied paint. Apply immediately after application of the last layer of lacquer.
	Dry accordingly to TDS recommendation of the respective clearcoat or solid colour.
	After use turn aerosol upside down and empty value.

The technical data contained herein is based on our present knowledge and we experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.